

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000701

International filing date: 25 February 2005 (25.02.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB
Number: 0404547.2
Filing date: 28 February 2004 (28.02.2004)

Date of receipt at the International Bureau: 26 April 2005 (26.04.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT/GB2005/000101
GB05/701



INVESTOR IN PEOPLE


The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



AEvens.

Signed

Dated 5 April 2005

Oct 1977




02MAR04 EB77272-1 B16563
P01/7700 0.00-0404547.2 NONE

1777

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

KAM002

2. Patent application number

(The Patent Office will fill in this part)

28 FEB 2004

0404547.2

3. Full name, address and postcode of the or of each applicant (underline all surnames)

KEVIN ANDREW MASON
CLOCK BARN FARM
HAMBLEDON ROAD
BUSBRIDGE
GODALMING
SURREY. GU8 4AY

KAM DIFFERENTIALS LTD
CLOCK BARN FARM
HAMBLEDON ROAD
BUSBRIDGE
GODALMING
SURREY
GU8 4AY

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

UK 08819641001

08819658001

4. Title of the invention

DIFFERENTIAL LOCKING SYSTEM

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

As Above.

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

N/A

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

N/A

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

NO

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d).

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

5

Claim(s)

4

Abstract

1

Drawing(s)

3 + m

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

I/We request the grant of a patent on the basis of this application.

11.

Signature

Kevin Mason

Date

27/2/02

12. Name and daytime telephone number of person to contact in the United Kingdom

KEVIN MASON,

01483

419779

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

Differential Locking System

5 This invention relates to a differential locking device for use with vehicles and to a method of installing a differential locking device onto a range of vehicle axles.

10 The differential locking assembly is an already well known and reliable component, particularly in the field of off road and agricultural vehicles. Many vehicles though, that are used for this type of work do not have them fitted and would greatly benefit by having them.

15 The after market differential locking systems presently available tend to be complicated and/or costly to produce and fit, particularly in the case of pneumatic, vacuum or cable systems. Also, the proposed system is not intrusive to the axle tubing itself, and therefore does not interfere with structural integrity of the axle assembly.

20 It is a feature of the present invention that it can provide a simple, cheap to produce device and system which is easy to install and, once fitted, is easy to inspect and adjust. The positioning of the locking assembly also has the advantage of not fouling any exhaust, brake line or suspension components etc. The system may also apply to a range of vehicles, be it new vehicles or retro fitting onto existing older vehicles.

25 The invention provides a differential pan removably attachable to a vehicle to cover the differential unit of the vehicle and a locking device able to be fitted to the differential unit of the vehicle in which, when the differential pan is attached to the vehicle, the locking device can be attached to the vehicle differential unit inside the differential pan.

Mounting a locking assembly under a removable differential cover creates an environment within the differential housing assembly, which has previously not been available, namely an area suitable to fit a differential locking device.

5 In a preferred method of installing the device of the invention to a vehicle a shaped mounting ring is fixed (preferably welded) onto the rear of the axle assembly of the vehicle, in place of the conventional differential pan. A removable differential cover, which is also sufficiently large enough to accept the complete locking assembly and actuator, is fitted to the mounting ring, encasing the entire assembly. A solenoid (or
10 other mechanical actuator device) is mounted inside the shaped ring, parallel to the half shaft of the vehicle to operate the locking device. The solenoid is connected to a fork, which in turn communicates reciprocal movement which engages/disengages a sliding dog gear (splined to the half shaft) into a splined bearing journal located in the differential carrier. This action causes the opposing half shafts to be locked together
15 or independent as desired.

It is a feature of the present invention that it is cheap to produce with very few components; it is versatile and can be fitted to the majority of different vehicles; can be installed on new vehicles or retrofitted. It is easy to install and easy to inspect and
20 adjust after assembly. Safety features which can be included are that, when the power is off, the device is unlocked and there can be an optional manual override.

A specific embodiment of the system will now be described by way of an example, with reference to the accompanying drawings. A retrofit example will be described
25 herein, but the same basic procedures and functions would also apply to production line new vehicles.

In the drawings

Fig. 1 is a plan view of the device

30 Fig. 2 is a view of the splines and locking components

Fig. 3 is a view of the actuator

Fig. 4 is a view of the differential carrier bearing

Fig. 5 shows material removed from the axle casing

Fig. 6 is a view of a manual override and

5 Figs. 7 and 8 shows a shaped differential pan.

Referring to figs. 1 to 4 the differential carrier core assembly (2) is fitted with a splined bearing journal (1) at one end. This journal will perform for both the diff carrier core and associated sun gear. This can be achieved by machining off the
10 original bearing journal at (3), internally splining the remaining casting (2) at position (9) and press fitting (interference fit) an externally splined bearing journal (1). A special half shaft is fitted with a lengthened spline shaft at the differential end. A sliding dog gear (5) with internal splines to match the half shaft is fitted onto the half shaft upon assembly. It also has external splines to match the differential carrier
15 splines, (although in some cases it is also preferable to have external splines on the differential carrier on an extended journal, and matching internal splines on the sliding dog.) The purpose of this sliding dog gear is to allow the half shaft to be connected to the differential carrier. The splines on the bearing journal and sliding dog are designed to easily mate.

20

To engage the differential lock, the sliding dog is forced inwards along the half shaft spline and locks into the spline previously mentioned in the differential carrier. This causes the two half shafts to be locked together, to create an even amount of drive to both connected half shafts, and thus turn the vehicle wheels evenly. The sliding dog's
25 movement in the example is caused by an electric solenoid (4), (Figure 3) (but any conventional assembly will also work), positioned parallel to the half shaft, mounted either above the differential carrier bearing (4) (Figure 4), or (as in this example) onto axle casing, opposed to the differential carrier (Figure 1A). Movement to the dog is communicated via a fork (6) connected to the solenoid.

30

The solenoid preloads a spring mounted in front of the fork (6) which in turn, transfers its energy to engage the dog gear into the differential carrier spline. A return spring is also installed to aid disengagement, in this example at (7).

5 To allow the above to be fitted into a conventional banjo type axle assembly, the old differential pan must firstly be removed (or not fitted in the case of a new vehicle). A special differential pan mounting ring (8), which is shaped to allow the fitment of the solenoid or actuator, is then fitted to the axle casing (10), in place of the old differential pan. This can have either threaded holes, studs or similar mountings
10 attached and must be substantial enough to reinforce the axle casing. If the ring is to be welded to the axle, mounting studs for the differential pan can be used to lift the ring away from the axle to create a space suitable for a welding bead, by protruding through the bottom of the ring. The axle assembly can then be reinstalled with differential and locking assembly.

15

Referring to fig. 5 in some cases there is not enough clearance between the axle housing and the differential bearing cap (1) to allow the fork to move fully. In these cases material can safely be removed from the axle casing (2), as the new differential pan mounting ring also acts as a reinforcing plate. The solenoid may also be mounted
20 on the ring at (3).

20

In the case of axles that already have removable differential pans, an adaptor plate may be fitted, utilising the existing holes in the axle case, to allow the new type of differential cover to be fitted, thus giving the space and environment needed to install
25 the system as described.

25

Referring to figures 7 and 8 a new shaped differential pan can then fitted, (1) along with a suitable gasket material, which allows the locking assembly to fit and operate. A simple electronic switch can be used to operate the system, via a warning lamp and
30 relay. The wiring must also be water resistant and located in such a position to not let

30

- 5 -

water into differential case or let oil out. An oil level plug to allow for new level of oil should also be added (2).

5 Referring to figure 6 a manual override can also be added to the unit. An example of this is to add a protruding rod (1) through the differential cover (2) & seal (3), which would communicate linear movement to the solenoid or actuator (4), which in turn would manually engage or disengage the locking dog, by locking lever (1) (through bush (7) in place by use of locking pin (5), into slots (6). This may be desirable in the case of an electrical failure within the vehicle.

10

It is proposed that ABS plastic would be a suitable material for the new differential pan, but steel or another material may also be practicable. If ABS is used, a steel guard may be desired. This could be fitted to the differential pan mounting ring giving additional strength to the differential pan. Reinforcing webs would also be a
15 desired feature, adding strength to the pan. The pan should also be made such that it can be used to cover the solenoid (or actuator) when it is fitted to either above the bearing caps or onto the axle casing.

20

Referring to figure 8 a magnetic sump plug (5) may also be added to ensure metallic particles do not foul in the solenoid and/or locking mechanism.

Claims

1. A differential pan removably attachable to a vehicle to cover the differential unit of the vehicle and a locking device able to be fitted to the differential unit of the vehicle in which, when the differential pan is attached to the vehicle, the locking device is able to be attached to the vehicle differential unit inside the differential pan.
2. A differential pan as claimed in claim 1 in which the locking device includes a mechanical actuator which acts on the locking device to operate the locking device.
3. A differential pan as claimed in claim 2 in which actuator is a solenoid.
4. A differential pan as claimed in claim 2 or 3 in which the actuator is adapted to be mounted on the axle casing, within the differential pan area.
5. A differential pan as claimed in claim 2 or 3 in which the actuator is adapted to be mounted onto a differential pan mounting ring.
6. A differential pan as claimed in one of the preceding claims in which the locking device comprises a fork which is able to communicate reciprocal movement which engages/disengages a sliding dog gear, splined to the half shaft of the vehicle, into a splined bearing journal located in the differential carrier.
7. A differential pan as claimed in any one of the preceding claims in which there is a ring or ring with an additional protrusion which can be fitted to the axle assembly to act as a mounting stage for an extended differential pan.
8. A differential pan as claimed in one of the preceding claims in which, when installed on a vehicle does not foul any of the vehicles services, such as brake lines,

exhaust pipes or suspension components etc. due to its positioning within differential pan.

5 9. A differential pan as claimed in one of the preceding claims which is constructed from an acrylonitrile/butadiene/styrene (ABS) plastics material

10 10. A vehicle having an axle incorporating a differential unit in which there is a differential locking pan and locking device as claimed in any one of the preceding claims.

11. A vehicle as claimed in claim 10 in which when there is a removable type of differential pan, there is provision for an extended area to accommodate the differential locking unit.

15 12. A vehicle as claimed in claim 10 or 11 in which there is a steel ring or ring with an additional protrusion, which is fitted to the axle assembly, which acts as a mounting stage for an extended differential pan.

20 13. A vehicle as claimed in any one of claims 10 to 12 in which there is a press-in bearing journal fitted into the differential carrier core, which incorporates a splined locking portion and also acts as a bearing journal for the sun gear of the differential unit.

25 14. A vehicle as claimed in any one of claims 10 to 13 in which the differential pan or locking device does not foul any of the vehicles services, such as brake lines, exhaust pipes or suspension components etc.

30 15. A vehicle as claimed in any one of claims 10 to 14 in which there is a manual override for the locking device.

16. A vehicle as in any one of claims 10 to 15 in which the actuator is mounted onto the differential unit bearing cap.

5 17. A vehicle as claimed in any one of claims 10 to 15 in which the actuator is mounted onto the axle casing, within the differential pan area.

18. A vehicle as claimed in any one of claims 10 to 15 in which the actuator is mounted onto the differential pan mounting ring.

10 19. A vehicle as claimed in any one of claims 10 to 18 in which the differential pan is removable to set up, inspect and/or adjust the differential lock assembly.

15 20. A vehicle as claimed in any one of claims 10 to 19 in which the axle casing material is reduced under differential pan to allow for locking component movement.

21. A vehicle as claimed in any one of claims 10 to 20 in which a differential pan mounting ring is used as reinforcement to the axle assembly.

20 22. A vehicle as claimed in any one of claims 10 to 19 in which there is a removable differential guard mounted onto the differential pan mounting ring bolts.

23. A vehicle as claimed in any one of claims 10 to 19 in which there are mounting studs used to create a space between mounting ring and axle assembly suitable for welding.

25 24. A method for fitting a differential pan as claimed in any one of claims 1 to 9 to a vehicle which comprises fixing a mounting ring onto the rear of the axle assembly of the vehicle, in place of the conventional differential pan, fitting the removable differential cover to the mounting ring to encase the entire assembly.

30

25. A method as claimed in claim 24 in which the mounting ring is attached to the rear of the axle assembly by welding.

5 26. A method as claimed in claim 24 or 25 in which a mechanical actuator device is mounted inside the shaped ring, parallel to the half shaft to operate the locking device which actuator is connected to a fork, which in turn communicates reciprocal movement which engages/disengages a sliding dog gear, splined to the half shaft, into a splined bearing journal located in the differential carrier.

10 27. A method as claimed in claim 26 in which the actuator is a solenoid.

28. A method as claimed in any one of claims 24 to 27 in which there are mounting studs used to create a space between mounting ring and axle assembly suitable for welding.

- 10 -

Abstract

5 A system of mounting differential locking devices onto a range of vehicles, be it new vehicles or retro fitting onto existing older vehicles, by means of mounting the locking assembly under a removable diff cover.

10 A shaped mounting ring is fixed onto the rear of the axle assembly, in place of a conventional diff pan. A removable diff cover, which is sufficiently shaped or enlarged to accept the locking actuator, is fitted to the mounting ring, encasing the whole diff and diff locking assembly.

15 A solenoid (or other mechanical actuator device) is mounted inside the shaped ring, parallel to the half shaft. The solenoid is connected to a fork, which in turn communicates reciprocal movement which engages/disengages a sliding dog gear into a splined bearing journal, press fitted into the diff carrier. This action causes the opposing half shafts to be locked together or independent as desired.






Figure 1a






Figure 3




Figure 4




Figure 5

3/3




Figure 6




Figure 7




Figure 8